## AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (previously presented) A high-voltage transformer provided with a bobbin in which frames of a primary-side winding and a secondary-side winding are provided on both sides of a frame of a magnetic-coupling adjusting winding to sandwich the frame of the magnetic-coupling adjusting winding, in order to make the frames of the primary-side winding, the secondary-side winding and the magnetic-coupling adjusting winding located in the same magnetic path,

wherein a first flange part is provided between the frame of the primary-side winding and the frame of the magnetic-coupling adjusting winding, and a second flange part is provided between the frame of the secondary-side winding and the frame of the magnetic-coupling adjusting winding, and

wherein a part of one of the primary-side winding and the secondary-side winding is wound around the frame of the magnetic-coupling adjusting winding through a notch part which is formed in the first flange part or the second flange part located on the lower surface side of the bobbin.

## 2 - 3. (canceled)

04/19/2006 Docket No.: KAW-347-PCT

S/N: TBA

- 4. (previously presented) The high-voltage transformer according to claim 1, wherein a part of the primary-side winding is wound around the frame of the magnetic-coupling adjusting winding to largely adjust the leakage inductance.
- 5. (previously presented) The high-voltage transformer according to claim 1, wherein a part of the secondary-side winding is wound around the frame of the magnetic-coupling adjusting winding to finely adjust the leakage inductance.
- 6. (currently amended) The high-voltage transformer according to any one of claims 1, 4, 5 claim 1, wherein pin-shaped terminals for substrate connection are provided for the bobbin, pin-shaped terminals extend in one direction substantially orthogonal to a direction in which the frames of the primary-side winding, the magnetic-coupling adjusting winding, and the secondary-side winding are arranged.